

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A method for disk I/O (input output) in a computer system, comprising:

upon receiving a request for a disk I/O from an application executing on the computer system, transferring a command to a disk controller, the command causing a start up of a disk drive coupled to the disk controller;

subsequent to transferring the command causing the start up and before the completion of said start up, preparing disk transaction information by packaging a plurality of data structures comprising a disk transaction;

transferring the disk transaction information to the disk controller; and  
implementing a disk I/O, wherein the disk controller uses the disk transaction information to control the disk drive.

2. (Original) The method of Claim 1, further comprising:

preparing the disk transaction information by using a processor of the computer system; and

transferring the disk transaction information from the processor to the disk controller.

3. (Original) The method of Claim 2, further comprising:

accessing a bus coupled to the disk controller to transfer the disk transaction information from the processor to the disk controller.

4. (Original) The method of Claim 3, further comprising:  
accessing a bridge component controlling the bus coupled to the disk controller and transferring the disk transaction information from the processor to the disk controller via the bridge component.

5. (Original) The method of Claim 4, wherein the bridge component is a South bridge of the computer system.

6. (Previously Presented) The method of Claim 1, wherein the transferring of the command to the disk controller causing the start up of the disk drive is configured to reduce a start up latency of the disk drive.

7. (Original) The method of Claim 1, wherein the disk transaction information includes a plurality of PRD (physical region descriptor) data structures and a plurality of CPB (command parameter block) data structures for implementing the disk transaction.

8. (Original) The method of Claim 1 wherein the disk drive is compatible with a version of the ATA standard.

9. (Previously Presented) A computer readable media having computer readable code which when executed by a processor of a computer system cause the computer system to implement a bypass method for efficient disk I/O (input output), comprising:

upon receiving a request for a disk I/O from an application executing on the computer system, transferring a command to a disk controller, the command causing a start up of a disk drive coupled to the disk controller;

subsequent to transferring the command causing the start up and before the completion of said start up, preparing disk transaction information by packaging a plurality of PRD (physical region descriptor) data structures and a plurality of CPB (command parameter block) data structures comprising the disk transaction;

accessing a bridge component controlling a bus coupled to the disk controller;

transferring the disk transaction information to a plurality of bypass registers of the disk controller via the bridge component; and

implementing a disk I/O, wherein the disk controller processes the disk transaction information to control the disk drive.

10. (Original) The computer readable media of Claim 9, wherein the bridge component is a South bridge of the computer system.

11. (Original) The computer readable media of Claim 10, further comprising:

accessing a North bridge to transfer the disk transaction information; and  
transferring the disk transaction information from the processor to the disk  
controller via the North bridge and the South bridge of the computer system.

12. (Previously Presented) The computer readable media of Claim 9,  
wherein the transferring of the command to the disk controller causing the start  
up of the disk drive is configured to hide a start up latency of the disk drive.

13. (Original) The computer readable media of Claim 9 wherein the disk  
drive is compatible with a version of the ATA standard.

14. (Previously Presented) A computer system for implementing a bypass  
method for efficient disk I/O (input output), comprising:

a processor;

a system memory coupled to the processor;

a bridge component coupled to the processor; and

a disk controller coupled to the bridge component, the disk controller  
including a plurality of bypass registers, wherein the processor executes software  
code stored in the system memory, the software code causing the computer  
system to implement a method comprising:

upon receiving a request for a disk I/O from an application executing on  
the computer system, transferring a command from the processor to the disk  
controller, the command causing a start up of a disk drive coupled to the disk  
controller;

subsequent to transferring the command causing the start up and before the completion of said start up, preparing disk transaction information by packaging a plurality of data structures comprising the disk transaction; transferring the disk transaction information to the bypass registers of the disk controller; and implementing a disk I/O, wherein the disk controller processes the disk transaction information to control the disk drive.

15. (Original) The system of Claim 14, further comprising:

preparing the disk transaction information by using a processor of the computer system; and

transferring the disk transaction information from the processor to the disk controller.

16. (Original) The system of Claim 14, wherein the disk controller is integrated within bridge component.

17. (Original) The system of Claim 14, wherein the bridge component is a South bridge of the computer system.

18. (Previously Presented) The system of Claim 14, wherein the transferring of the command to the disk controller causing the start up of the disk drive is configured to reduce a start up latency of the disk drive.

19. (Original) The system of Claim 14, wherein the disk transaction information includes a plurality of PRD (physical region descriptor) data structures and a plurality of CPB (command parameter block) data structures for implementing the disk transaction.

20. (Original) The system of Claim 14 wherein the disk drive is compatible with a version of the ATA standard.

21. (Previously Presented) The system as described in Claim 20, wherein said plurality of bypass registers is operable to allow said disk controller to implement a disk transaction without writing to a register of said ATA standard.

22. (Previously Presented) The method as described in Claim 1 further comprising:

aggregating said transaction information via a memory mapped data transfer from a processor of said computer system.